



E2E-X2B1T8-M5

Sensore di prossimità induttivo, M8, acciaio inox, corpo corto, schermato, 2 mm, DC, 3 fili, PNP NA, IO-Link COM3, connettore M8 (3 pin)

Specifiche

Size	M8
Mounting type	Flush
Sensing distance	2 mm
Overall length of sensor	39 mm
Thread length	22 mm
Material housing	Stainless steel
Output type	IO-Link, PNP
Operation mode	NO
Connection method	Connector M8 - 3 pin
Cable specifications	-
IO-Link function	✓
IO-Link baud rate	COM3 (230.4 kbps)
Degree of protection (IP)	IP67/IP69K

Prodotti



Connettori e set di cavi M8

Connettori e set di cavi industriali per qualsiasi applicazione

Libreria CAD



E2E NEXT Catalogo tecnico

EN PDF 40 MB



E2E(Q) - Basic Models Elenco indice

EN PDF 7,27 MB



E2E(Q) - Premium Models Elenco indice

EN PDF 719 KB



E2E(Q)- XB_XC_basic_model Foglio istruzioni

EN PDF 2,28 MB



E2E[Q]-XxBxxxx File IO-Link IODD

EN ZIP 1,35 MB



E2E_Q DC 3-wire Eu declaration of conformity

EN PDF 130 KB



IO-Link Series Brochure

IT PDF 4,08 MB