



# MASTER PL-C 4 Pin

## MASTER PL-C 26W/840/4P 1CT/5X10BOX

MASTER PL-C is an efficient medium-wattage compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 4-pin version is designed for operation on electronic HF control gear with integrated pre-heat and is provided with a plug-in/pull-out lamp base.

### Product data

General Information		LLMF 6000 h Rated		LLMF 8000 h Rated	
Cap-Base	G24Q-3 [ G24q-3]		83 %		81 %
Life To 50% Failures Preheat (Nom)	13000 h				
LSF Preheat 2000 h Rated	99 %	<b>Operating and Electrical</b>			
LSF Preheat 4000 h Rated	98 %	Power (Rated) (Nom)	26.0 W		
LSF Preheat 6000 h Rated	97 %	Lamp Current (Nom)	0.335 A		
LSF Preheat 8000 h Rated	90 %	<b>Temperature</b>			
		Design Temperature (Nom)	28 °C		
		<b>Controls and Dimming</b>			
		Dimmable	Yes		
		<b>Mechanical and Housing</b>			
		Cap-Base Information	4 Pins		
		<b>Approval and Application</b>			
		Energy Efficiency Label (EEL)	A		
		Mercury (Hg) Content (Nom)	1.4 mg		
<b>Light Technical</b>					
Color Code	840 [ CCT of 4000K (841)]				
Luminous Flux (Nom)	1800 lm				
Luminous Flux (Rated) (Nom)	1800 lm				
Color Designation	Cool White (CW)				
Chromaticity Coordinate X (Nom)	380				
Chromaticity Coordinate Y (Nom)	380				
Correlated Color Temperature (Nom)	4100 K				
Luminous Efficacy (rated) (Nom)	67 lm/W				
Color Rendering Index (Nom)	82				
LLMF 2000 h Rated	92 %				
LLMF 4000 h Rated	87 %				

# MASTER PL-C 4 Pin


Energy Consumption kWh/1000 h	29 kWh
<b>Product Data</b>	
Full product code	871150062336200
Order product name	MASTER PL-C 26W/840/4P 1CT/5X10BOX
EAN/UPC - Product	8711500623362
Order code	927907384002

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material Nr. (12NC)	927907384002
Net Weight (Piece)	60.400 g
ILCOS Code	FSQ-26/40/1B-E-G24q=3

## Warnings and Safety

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied HF control gear
- Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.



## Dimensional drawing



Product	D	D1	A	B	C
MASTER PL-C 26W/840/4P 1CT/ 5X10BOX	27.1 mm	27.1 mm	130.5 mm	149.0 mm	163.9 mm

PL-C 26W/840/4P

## Photometric data



## MASTER PL-C 4 Pin

